
Rack and pinion actuator EA-SZ 230/65/550



Technical Data

Input voltage	230 V AC
Nominal current	0.22
Running speed	9
IP code	IP55
Switch on duration	20

MOUNTING POSITIONS



TECHNICAL DATA

Matchcode	EA-SZ 230/65/550
Article name	Rack and pinion actuator EA-SZ 230/65/550
Part number	M2 1081 A
Input voltage	230 V AC
Nominal current	0.22
Stroke	550
Push force	650
Pull force	650
Cut-Off	integrated overload cut-off
Running speed	9
IP code	IP55
Switch on duration	20
Mounting way	aufgesetzt
Weight	2.95
Housing	Rack housing: anodized aluminum E6 / EV1, gray motor housing: plastic, stroke + 220 mm x 54 x 120 mm
Housing type	Aluminium
Colour	On request
Housing length	220
Housing width	54
Housing height	120
Connection cable	Silicone cable 4 x 0.75 mm², white, Length 1,500 mm

Rack and pinion actuator EA-SZ 230/65/550

Nominal working temperature	20
Environment temperature range	-10 °C - 60 °C
Brackets included	ja

ACCESSORIES

Part no.	Matchcode	
M2 1083	EA-SZ-M-350	
M2 1083 A	EA-SZ-VERBIND-1	
M2 1083 B	EA-SZ-VERBIND-2	
M2 1084	EA-SZ-M-550	
M2 1089	EA-SZ-M-750	
M2 1091	EA-SZ-M-1000	