



Technical Data



| | |
|--------------------|----------|
| Input voltage | 230 V AC |
| Nominal current | 0.23 |
| Running speed | 9.7 |
| IP code | IP32 |
| Switch on duration | 30 |

MOUNTING POSITIONS



TECHNICAL DATA

| | |
|-------------------------------|---|
| Matchcode | EA230-K-30/1000-S |
| Article name | chain actuator EA230-K-30/1000-S |
| Part number | M2 5147 |
| Input voltage | 230 V AC |
| Nominal current | 0.23 |
| Input voltage range | - 10 % / + 10 % |
| Stroke | 1000 |
| Push force | 300 |
| Pull force | 300 |
| Nominal locking force | 2000 |
| Cut-Off | Integrated electronic overload cut-off |
| Running speed | 9.7 |
| IP code | IP32 |
| Switch on duration | 30 |
| Mounting way | aufgesetzt |
| Weight | 2.2 |
| Housing | Aluminium profile housing E6/EV1 anodized |
| Housing type | Aluminium |
| Colour | On request |
| Housing length | 824 |
| Housing width | 35 |
| Housing height | 37 |
| Appliance class | III |
| Connection cable | plastic connection cable, 5 x 0.5 mm ² , white, length 2.5 m |
| Nominal working temperature | 20 |
| Environment temperature range | 0 °C - 75 °C |
| Brackets included | nein |

ACCESSORIES

| Part no. | Matchcode | |
|-------------------------|-----------------------------|--|
| K2 5089 | K-K50-OK | |
| K2 5097 | K-K30-A | |
| K2 5098 | K-K30-K | |
| K2 5104 | K-K30-FLEX | |
| K2 5105 | K-K30-AKI | |
| K2 5106 | K-K-OK-SK | |
| K2 5107 | K-K30-ZB | |
| K2 5108 | K-K30-AKI-R | |