



### Technical Data



Input voltage	230 V AC
Output voltage	24 V DC
Output current	10

### TECHNICAL DATA

Matchcode	M-VENT-10-AP (2 FMU)
Article name	Ventilation control unit M-VENT-10-AP
Part number	ST4 4041
Input voltage	230 V AC
Output voltage	24 V DC
Output current	10
LED signs	white: WTS; yellow: failure; green: OK
IP code	IP20
Weight	4.5
Housing	Sheet steel housing 301 x 323 x 85 mm (WxHxD), surface-mounting
Housing type	Steel case
Colour	RAL 9010 white
Housing width	301
Housing height	323
Housing depth	85
Environment temperature range	-5°C - +60°C

### ACCESSORIES

Part no.	Matchcode
<a href="#">ST4 10120</a>	<a href="#">Pb-battery-7Ah</a>
<a href="#">ST4 10121</a>	<a href="#">pb-battery-12ah</a>
<a href="#">ST4 10122</a>	<a href="#">pb-battery-17ah</a>
<a href="#">ST4 10123</a>	<a href="#">pb-battery-24ah</a>
<a href="#">ST4 10124</a>	<a href="#">Pb battery 38 Ah</a>
<a href="#">ST4 3321</a>	<a href="#">Flange plate 445-130 plastic</a>
<a href="#">ST4 3322</a>	<a href="#">Flange plate 345-130 plastic</a>
<a href="#">ST4 3323</a>	<a href="#">Flange plate 545-130 plastic</a>
<a href="#">ST4 3344</a>	<a href="#">HR-820-MS</a>
<a href="#">ST4 3361</a>	<a href="#">Charge electronics, type LB-120</a>
<a href="#">ST4 3362</a>	<a href="#">Charge electronics, type LB-140</a>
<a href="#">ST4 3363</a>	<a href="#">Charge electronics, type LB-160</a>

<a href="#">ST4 3369</a>	<a href="#">Charge electronics, type LB-120-10</a>
<a href="#">ST4 3380</a>	<a href="#">ZI-100</a>
<a href="#">ST4 3381</a>	<a href="#">SI-100</a>
<a href="#">ST4 3382</a>	<a href="#">MI-100</a>
<a href="#">ST4 3383</a>	<a href="#">MR-120</a>
<a href="#">ST4 3385</a>	<a href="#">MI-100-MB</a>
<a href="#">ST4 3386</a>	<a href="#">SI-100-MASTER</a>
<a href="#">ST4 3389</a>	<a href="#">BI-100-KNX</a>