
Chain acutator EA-K-65/300-T



Technical Data

Input voltage	24 V DC
Nominal current	1.9
Running speed	13.7
IP code	IP32
Switch on duration	30

MOUNTING POSITIONS



TECHNICAL DATA

Matchcode	EA-K-65/300-T
Article name	Chain acutator EA-K-65/300-T
Part number	M2 5325 T
Input voltage	24 V DC
Nominal current	1.9
Input voltage range	- 15 % / + 15 %
Stroke	300
Push force	650
Pull force	650
Nominal locking force	700
Cut-Off	Integrated electronic load shutdown
Running speed	13.7
IP code	IP32
Switch on duration	30
Mounting way	aufgesetzt
Weight	1.96
Housing	Aluminum profile housing EV1 anodized
Housing type	Aluminium
Housing length	430
Housing width	50
Housing height	41
Appliance class	III
Connection cable	Silicone connection cable 6 x 0.75 mm² (length 3,000 mm)
Nominal working temperature	20
Environment temperature range	-5 °C - 75 °C
Brackets included	nein

Chain acutator EA-K-65/300-T

ACCESSORIES

Part no.	Matchcode	
K2 5088	K-K50-SKI	
K2 5089	K-K50-OK	
K2 5090	K-K50-AKI	
K2 5092	K-K50-A	
K2 5093	K-K50-K	
K2 5094	K-K50-FLEX	
K2 5106	K-K-OK-SK	