



## Technical Data



|                    |         |
|--------------------|---------|
| Input voltage      | 24 V DC |
| Nominal current    | 1.1     |
| Switch on duration | 30      |

### TECHNICAL DATA

|                               |  |
|-------------------------------|--|
| Matchcode                     | ZVK-LOCK-I   |
| Article name                  | Supplementary electric locking ZVK-LOCK-I  |
| Part number                   | B5 6140  |
| Input voltage                 | 24 V DC  |
| Output voltage                | 24 V DC  |
| Nominal current               | 1.1  |
| Input voltage range           | - 15 % / + 15 %  |
| Ripple                        | 500  |
| Stroke                        | 18 / 36  |
| Nominal locking force         | 300  |
| Cut-Off                       | built-in electronic overload cut-off Overload protection: electronic Max. switching current of follower actuators: 6 A |
| IP code                       | IP32   |
| Switch on duration            | 30   |
| Mounting way                  | aufgesetzt   |
| Weight                        | 0.47   |
| Housing                       | Aluminium  |
| Housing type                  | Aluminium  |
| Housing length                | 377  |
| Housing width                 | 26   |
| Housing height                | 26   |
| Appliance class               | III  |
| Connection cable              | 5-pin plug without connection cable  |
| Nominal working temperature   | 20   |
| Environment temperature range | -5 °C - +70 °C   |