



Technical Data



Input voltage	24 V DC
Nominal current	1.6
Opening angle	125
IP code	IP54
Switch on duration	30

MOUNTING POSITIONS



TECHNICAL DATA

Matchcode	EA-KL ² -T-K-50-DC
Article name	Folding arm ² door opener EA-KL ² -T-K-50-DC
Part number	M2 1520
Input voltage	24 V DC
Nominal current	1.6
Input voltage range	- 15 % / + 15 %
Ripple	500
Opening angle	125
Push force	500
Pull force	50
Classification	tested and certified according to EN 12101-2, incl. continuous operation RE 1000.
Cut-Off	integrated electronic overload cut-off
Running speed	2
IP code	IP54
Switch on duration	30
Mounting way	aufgesetzt
Weight	4.22
Housing	Aluminium housing E6 / EV1 anodized
Housing type	Aluminium
Colour	RAL & DB colors
Housing length	474
Housing width	58
Housing height	118

Appliance class	III
Connection cable	Silicone connection cable 6 x 0.75 mm ² , light gray, length 3,000 mm
Nominal working temperature	20
Environment temperature range	0 °C - 75 °C
Brackets included	nein

ACCESSORIES

Part no.	Matchcode
K2 1620	K-KL²-T-MW
K2 1621	K-KL²-T-MP
SD1 8522	SICO-LINK-Adapter
SD1 8525	SICO-PLUCKER
SD1 8530	Software parameterization