



**Technical Data**



Input voltage	24 V DC
Nominal current	1.0
Running speed	7.7
IP code	IP54
Switch on duration	30

**MOUNTING POSITIONS**



**TECHNICAL DATA**

Matchcode	PA-LSA-50/200-S
Article name	Slit actuator PA-LSA-50/200-S
Part number	M2 2461 S A
Input voltage	24 V DC
Nominal current	1.0
Input voltage range	- 15 % / + 15 %
Stroke	181
Push force	500
Pull force	500
Nominal locking force	1000
Cut-Off	Integrated electronic overload cut-off
Running speed	7.7
IP code	IP54
Switch on duration	30
Mounting way	aufgesetzt
Weight	1.9
Housing	End-to-end aluminium profile tube, anodized in E6/EV1 with integrated retainer for flexible bracket system
Housing type	Aluminium
Colour	On request
Housing length	535
Housing height	42
Diameter	36

Appliance class	III
Connection cable	SICO PLUG connection. Excluding connection cable / set.
Nominal working temperature	20
Environment temperature range	-5 °C - 75 °C
Brackets included	nein
Customs tariff no	84798997

**ACCESSORIES**

Part no.	Matchcode
<a href="#">K2 1501</a>	<a href="#">OK</a>
<a href="#">K2 1502</a>	<a href="#">DAS</a>
<a href="#">K2 1505 A</a>	<a href="#">UKU-740</a>
<a href="#">K2 1539</a>	<a href="#">HK-L</a>
<a href="#">K2 1562</a>	<a href="#">UK-L</a>
<a href="#">K2 1563</a>	<a href="#">K-L-UK-J</a>
<a href="#">K2 1576</a>	<a href="#">K-L-RAICO105D-RE-9006 (rechts)</a>
<a href="#">K2 1577</a>	<a href="#">K-L-RAICO105D-LI-9006 (links)</a>
<a href="#">K2 1601</a>	<a href="#">K-L-A-LI-AW57RO</a>
<a href="#">K2 1603</a>	<a href="#">K-L-A-RE-AW57RO</a>
<a href="#">K2 2004</a>	<a href="#">PA-ANL-3m</a>
<a href="#">K2 2005</a>	<a href="#">PA-ANL-5m</a>
<a href="#">K2 2006</a>	<a href="#">PA-ANL-+lfm</a>
<a href="#">K2 2007</a>	<a href="#">PA-SICO-SET-3m</a>
<a href="#">K2 2008</a>	<a href="#">PA-SICO-SET-5m</a>
<a href="#">K2 2009</a>	<a href="#">PA-SICO-SET-+lfm</a>
<a href="#">SD1 8522</a>	<a href="#">SICO-LINK-Adapter</a>
<a href="#">SD1 8525</a>	<a href="#">SICO-PLUCKER</a>